



## 1717L 17" LCD Desktop Touchmonitor

**The Elo Touch Solutions 1717L is a flexible, space-saving, standard aspect ratio 17-inch LCD touchmonitor** well-suited to meet the durability and aesthetic requirements for front-of-store, back office, kiosk and even out-of-store applications.

The Elo 1717L offers true versatility for a variety of retail and hospitality interactive solutions including:

- Point-of-sale (POS)
- Point-of-service
- Loyalty systems
- Countertop kiosk point-of-information
- Back office solutions integrating labor management and inventory analysis
- Shelf-level/countertop interactive digital signage displays

Available with a choice of two zero-bezel touchscreen technologies, iTouch surface acoustic wave or AccuTouch resistive, the 1717L provides stable, "drift-free" operation with excellent image clarity, resolution, and light transmission—for an accurate touch response and vivid images! The 1717L is distinctive by incorporating state-of-the-art LED backlights that reduce the energy consumption of the higher energy consumption of CCFL backlights often used by other touchmonitors.

### Features and Benefits

- Choice of two leading Elo zero-bezel touchscreen technologies:
  - iTouch surface acoustic wave
  - Zero-bezel AccuTouch resistive
- Zero-bezel touchscreen for seamless, easy-to-clean glass-to-edge design
- 5:4 aspect ratio panel
- USB touch controller, VGA port
- LED backlighting allows for state-of-the-art slim design, while reducing power consumption
- Removable base and mounting features, including a VESA mount as well as wall- and arm-mounting options for installation flexibility
- Ruggedized for use in high-traffic environments
- Optional peripherals include field-installable 3-stripe Magnetic Stripe Reader (MSR), Rear Facing Customer Display (RFCD) and various display stands
- Up to 1280 x 1024 resolution at 75Hz
- Mounting holes on base bottom for tabletop security
- Controls on the side, plus lockout function for public use
- Digital on-screen display (OSD)
- Worldwide agency approvals

# 1717L 17" LCD Desktop Touchmonitor

## Computer Specifications

Model	1717L
Color	Black or white
Active Display Area	13.3" x 10.6" (337.9mm x 270.3mm)
Dimensions* (without stand and packaging)	15.42" x 12.88" x 1.91" (391.9mm x 327.2mm x 48.6mm) max
LCD Technology	Active matrix TFT LCD
Diagonal Size	17"
On-Screen Display (OSD)	Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Video Source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Mounting Options*	VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Preset Video Timings	640 x 480 60Hz,75Hz; 720 x 400 70Hz; 800 x 600 56, 60Hz,75Hz; 1024 x 768 60Hz,75Hz; 1280x1024 60Hz,75Hz
Number of Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits; with iTouch: 225 nits; with AccuTouch: 200 nits
Response Time (Tr + Tf) (typical)	8ms
Viewing Angle (typical)	Horizontal: 170°; Vertical: 160°
Contrast Ratio (typical)	800:1
Video	Analog VGA on Female DE-15 connector; Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	Monitor input power connector: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC $\pm$ 5%. Note: This monitor is sold with an AC-DC power adapter. Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor + AC/DC adapter): 21W; SLEEP (monitor + AC/DC adapter): 1.1W; OFF (monitor + AC/DC adapter): 1.0W
Weight (with stand)	Unpackaged: 12.1 lbs (5.5kg); Packaged: 16.5 lbs (7.5kg)
Weight (without stand and packaging)	8.5 lbs (3.87kg)
Shipping Dimensions	18.5" x 16.7" x 8.89" (471mm x 426mm x 226mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; BSMI Mark; UL, FCC; CB; RoHS, China RoHS, WEEE, IMERC
Warranty	3 years
MTBF	50,000 hours demonstrated

\*See dimensional drawings for details

For updated specifications and more information, please visit [www.elotouch.com](http://www.elotouch.com).

To find out more about our extensive range of Elo touch solutions, go to [www.elotouch.com](http://www.elotouch.com), or call the office nearest you.

### North America

Elo Touch Solutions  
301 Constitution Drive  
Menlo Park, CA 94025-1110  
800-ELO-TOUCH  
Tel 1-650-361-4800  
Fax 1-650-361-4722  
[customerservice@elotouch.com](mailto:customerservice@elotouch.com)

### Europe

Tel +32 (0)16 35 21 00  
Fax +32 (0)16 35 21 01  
[elosales@elotouch.com](mailto:elosales@elotouch.com)

### Asia-Pacific

Tel +81 (45) 478-2161  
Fax +81 (45) 478-2180  
[www.tps.co.jp](http://www.tps.co.jp)

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
[www.elotouch.com.ar](http://www.elotouch.com.ar)

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and iTouch are trademarks of Elo Touch Solutions, Inc.  
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 07/12